

Series NPS Push Stations



Features:

- UL 2017 Listed switch assembly
- Available in five colors: Red, Green, Yellow, White, or Blue
- Custom wording available
- Polycarbonate faceplate
- · Stainless steel backplate
- ADA Compliant
- Mounts to single gang electrical box
- Interchangeable or replaceable Normally Open (NO) and Normally Closed (NC) Single Pole, Single Throw gold plated contact blocks rated for 3 amps @ 600 VAC or 1 amp @ 250 VDC
- Can be reset by depressing the "Push" button, and turning clockwise a ¼ turn
- Comes with one (NO) contact and one (NC) contact
- Measurements: 5" H x 3¼" W x 1½ D

Description:

Multipurpose push stations for manual activation of SAFEPATH[®] and SAFEPATH[®]4 Voice Evacuation Systems prerecorded messages. Can be used to manually activate a message in the event of an emergency or for alerting.

Applications:

- For use with and SAFEPATH®4 Multifunction Facility Communications System
- Manual activation of messages in the event of an emergency
- Manual activation of messages to alert or warn others

Architects and Engineers Specifications

Push stations shall be designed for manual activation of SAFEPATH[®]4 Voice Evacuation Facility Communications System prerecorded messages. The faceplate shall be constructed of polycarbonate. The backplate shall be stainless steel. The switch assembly shall be a UL Standard 2017 listed Normally Open (NO) and Normally Closed (NC) Single Pole, Single Throw gold plated contact blocks rated for 3 amps @ 600 VAC or 1 amp @ 250 VDC. The push stations shall be ADA compliant. The push stations shall mount to a single gang electrical box. The push station shall be capable of being reset by depressing the "Push" button, and turning clockwise a ¼ turn. The push stations shall be available in five colors: red, green, yellow, white or blue. Custom word printing on the top of the push station shall be available.

Ordering Information

Model Number	Order Code	Color	Description	
NPS-R	9767	Red	Push Station for manual message activation	
NPS-G	9768	Green		
NPS-Y	9769	Yellow		
NPS-W	9770	White		
NPS-B	9771	Blue		
NPS-NO	0523		Push Station Normally Open Contact	
NPS-NC	0524		Push Station Normally Closed Contact	

Wording Matrix for top of the Push Station

Any "wording suffix" can be printed on any color push station.

Examples:

9767-003	NPS-R-003	Red Push Station, Colors
9771-010	NPS-B-010	Blue Push Station, Low

Note: Custom wording is available, please contact customer service.

Wording	Model Code Suffix	Wording	Model Code Suffix	
Land Attack	-001	Emergencia	-026	
Sea Attack	-002	Alarm Yellow	-027	
Colors	-003	Delta	-028	
Low Threat	-004	Alarm Red	-029	
Medium Threat	-005	Withdrawel	-030	
High Threat	-006	Emergency	-031	
Small Craft	-007	Audio Test	-032	
Unknown Object	-008	All Clear	-033	
Code Bravo	-009	Fire Test	-034	
Low	-010	Evac Drill	-035	
Medium	-011	Weather	-036	
High	-012	Chem-Bio	-037	
Water Attack	-013	Suspicious	-038	
Chemical Spill	-014	Fire*	-039	
Gas Release	-015	All	-040	
Evacuation	-016	Bomb	-041	
Help	-017	Test	-042	
Assistance	-018	Area	-043	
Severe Weather	-019	Bomb Threat	-044	
Tornado	-020	Terrorist Threat	-045	
Medical Alert	-021	Toxic Chemical	-046	
Power Shut Down	-022	Disaster	-047	
Blank / No Wording	-023	*For non UL Life Safety Applications		
Strobe	-024			
Alert	-025			



WE ENCOURAGE AND SUPPORT NICET CERTIFICATION 3 YEAR WARRANTY Made in USA V2004 NPS 02/08

NJ Location 273 Branchport Ave. Long Branch, NJ 07740 P: 800-631-2148 F: 732-222-8707 www.coopernotification.com FL Location 7565 Commerce Ct. Sarasota, FL 34243 P: 941-487-2300 F: 941-487-2389 VA Location P: 877-459-7726 F: 703-294-6560



Cooper Notification is Wheelock[®] (MEDC) SAFEPATH[®] WAVES